



SLIP ON LOCK NUTS

ZINC




TABLE 1: SIZING INFORMATION

ROD DIAMETER	A	B	C	D	WEIGHT #100
1/4" (6MM)	20	0.625	0.715	0.375	2.08
5/16" (8MM)	18	0.750	0.865	0.375	3.40
3/8" (10MM)	16	0.875	1.010	0.490	5.50
1/2" (12/14MM)	13	1.062	1.226	0.625	9.90
5/8" (16/18MM)	11	1.312	1.515	0.650	15.6
3/4" (20MM)	10	1.625	1.876	0.800	0.310 each
7/8" (22MM)	9	2.000	2.309	1.000	0.570 each
1" (24MM)	8	2.000	2.309	1.000	0.550 each

Technical information is substantiated by independent test laboratory reports

TABLE 2: TECHNICAL INFORMATION

PART NUMBER	SIZE	RECOMMENDED LOADS	RECOMMENDED TORQUE	FEDERAL STOCK # FOR GOVERNMENT USE
2SLN1420	1/4"-20	650 lbs.	6-8 ft. lbs.	#5310-01-264-0918
2SLN3816	3/8"-16	2,000 lbs.	19-25 ft. lbs.	#5310-01-268-5154
2SLN1213	1/2"-13	4,000 lbs.	50-60 ft. lbs.	#5310-01-268-5155
2SLN5811	5/8"-11	5,000 lbs.	100-200 ft. lbs.	#5310-01-268-5156
2SLN3410	3/4"-10	8,000 ft. lbs.	180-200 ft. lbs.	#5310-01-268-5157