

VF200PRO

ADHESIVE INJECTION

CERTIFICATION

MATERIAL SAFETY DATA



ICC-ESR 4632
Evaluated



FOR INSTALL SUPPORT
sales@allfasteners.com



FOR SPECIFICATION SUPPORT
certs@allfasteners.com



FOR CUSTOMER SUPPORT
888.859.6060





VF200PRO ADHESIVE INJECTION

PART A

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: VF200PRO Versatile High-Load Adhesive Injection - PART A

1.2 RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Use of the substance/mixture: Adhesive mortar for fastening elements A-component (resin)

Uses advised against: No restriction

1.2 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier:	Allfasteners USA, LLC.	Fax: 201-783-8840
	480 Meadow Lane, Carlstadt, NJ 07072	Email: sales@allfasteners.com
	Phone: 888.859.6060	www.Allfasteners.com

1.3 EMERGENCY PHONE NUMBER

Emergency Telephone: 888.859.6060

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

29 CFR Part 1910.1200: Respiratory or skin sensitization: Skin Sens. 1
Specific target organ toxicity single exposure: STOT SE 3 (respiratory tract irritation)

2.2 LABEL ELEMENTS

29 CFR Part 1910.1200:

Hazard Pictograms:



Signal Word: Warning

Hazard Statements: May cause an allergic skin reaction
May cause respiratory irritation

Precautionary statements: If medical advice is needed, have product container or label at hand.
Keep out of reach of children.

**VF200PRO ADHESIVE INJECTION**

PART A

2.2 LABEL ELEMENTS CONTINUED

Precautionary statements:	Warning
	May cause an allergic skin reaction
	May cause respiratory irritation
	If medical advice is needed, have product container or label at hand.
	Keep out of reach of children.
Hazards not otherwise classified:	Use only outdoors or in a well-ventilated area.
	Wear protective gloves/protective clothing/eye protection/face protection.
	If skin irritation or rash occurs: Get medical advice/attention.
	Wash contaminated clothing before reuse.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 MIXTURES****TABLE 1: MIXTURES**

HAZARDOUS COMPONENTS		
CAS NO.	COMPONENTS	QUANTITY
97-90-5	ethylene dimethacrylate	11.69 %
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	6.677 %
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol	0.9682 %

SECTION 4: FIRST-AID MEASURES**4.1 DESCRIPTION OF FIRST AID MEASURES**

General information:	Take off immediately all contaminated clothing and wash it before reuse.
After inhalation:	Provide fresh air. When in doubt or if symptoms are observed, get medical advice.
After contact with skin:	Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.
After contact with eyes:	Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.
After ingestion:	Rinse mouth immediately and drink plenty of water.

Most important symptoms and effects, both acute and delayed: Allergic reactions**Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

**VF200PRO ADHESIVE INJECTION**

PART A

SECTION 5: FIRE-FIGHTING MEASURES**5.1 EXTINGUISHING MEDIA**

Suitable extinguishing media: Extinguishing powder. Water spray jet.

Unsuitable extinguishing media: Full water jet

5.2 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Pyrolysis products, toxic. Carbon monoxide.

5.3 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE - FIGHTERS

In case of fire and/or explosion do not breathe fumes. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 ADDITIONAL INFORMATION

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

Provide adequate ventilation. Do not breathe gas/fume/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2 ENVIRONMENTAL PRECAUTIONS

Do not allow to enter into surface water or drains.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4 REFERENCE TO OTHER SECTIONS

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13



VF200PRO ADHESIVE INJECTION

PART A

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Advice on safe handling:

Use only outdoors or in a well-ventilated area.
When using do not eat, drink or smoke.
Wash hands before breaks and after work.

Advice on protection against fire
and explosion:

No special fire protection measures are necessary.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Requirements for storage rooms and vessels: Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place.

Advice on storage compatibility: Do not use for products which come into contact with the food stuffs.

Further information on storage conditions: Storage temperature : 5-25°C

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS & EXPOSURE LIMITS

TABLE 2: CONTROL PARAMETERS & EXPOSURE LIMITS

EXPOSURE LIMITS						
CAS NO.	SUBSTANCE	PPM	MG/M ³	F/CC	CATEGORY	ORIGIN
14808-60-7	Silica, crystalline (as respirable dust)	-	0.05		TWA (8 h)	REL
14808-60-7	Silica, crystalline quartz, respirable dust	(Z-3)	(Z-3)		TWA (8 h)	PEL
14808-60-7	Silica, crystalline quartz, total dust		(Z-3)		TWA (8 h)	PEL

Additional advice on limit values: The contained quartz is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded.

8.2 EXPOSURE CONTROLS



Protective and hygiene measures: Remove contaminated, saturated clothing immediately. Draw up and observe skin protection program. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection: Wear eye protection/face protection.

**VF200PRO ADHESIVE INJECTION**

PART A

8.2 EXPOSURE CONTROLS CONTINUED

Hand protection: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,4mm NBR (Nitrile rubber) >480min (EN374)

Wearing time with permanent contact 0,5mm NBR (Nitrile rubber) >480min (EN374)

Skin protection: Wear suitable protective clothing.

Respiratory protection: In case of inadequate ventilation wear respiratory protection.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Paste	Oxidizing properties	Not oxidising.
Color:	Light beige	Vapor pressure:	Not determined.
pH-Value:	Not determined.	Density (at 20 °C):	1,71 g/cm ³
Changes in the physical state		Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Melting point/freezing point:	Not determined.		
Initial boiling point & boiling range:	Not determined.		
Flash point:	Not applicable.		
Flammability		Solubility in other solvents	Not determined.
Solid:	Not determined.	Partition coefficient:	Not determined.
Gas:	Not applicable.	Vapor density:	Not determined.
Lower explosion limits:	Not determined.	Evaporation rate:	Not determined.
Upper explosion limits:	Not determined.		
Auto-ignition temperature		Other information	
Solid:	Not determined.	Solid content:	Not determined.
Gas:	Not applicable.		
Decomposition temperature:	Not determined.		



VF200PRO ADHESIVE INJECTION

PART A

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	No hazardous reaction when handled and stored according to provisions.
Chemical Stability:	The product is stable under storage at normal ambient temperatures.
Possibility of hazardous reactions:	No known hazardous reactions.
Conditions to avoid:	none/none
Incompatible materials:	No information available.
Hazardous decomposition products:	No known hazardous decomposition products.

SECTION 11: TOXICOLOGICAL INFORMATION & EFFECTS

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

TABLE 3: INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY					
CAS NO.	COMPONENTS				
	Exposure route	Dose	Species	Source	Method
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 11200 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol				
	oral	LD50 27,5 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg			

Carcinogenicity (IARC): Silica dust, crystalline, in the form of quartz or cristobalite (CAS 14808-60-7) is listed in group 1.

Aspiration hazard: The contained quartz is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded.

Further information: The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

**VF200PRO ADHESIVE INJECTION**

PART A

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	The product is not: Ecotoxic.
Persistence and degradability:	The product has not been tested.
Bioaccumulative potential:	The product has not been tested.
Mobility in soil:	The product has not been tested.
Other adverse effects:	No information available.
Further information:	Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 WASTE TREATMENT METHODS**

Advice on disposal: Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging: Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: TRANSPORT INFORMATION**US DOT 49 CFR 172.101**

Proper shipping name: Not a hazardous material with respect to these transport regulations.

Marine transport (IMDG)

UN number: No dangerous good in sense of this transport regulation.

UN proper shipping name: No dangerous good in sense of this transport regulation.

Transport hazard class(es): No dangerous good in sense of this transport regulation.

Packing group : No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number: No dangerous good in sense of this transport regulation.

UN proper shipping name: No dangerous good in sense of this transport regulation.

Transport hazard class(es): No dangerous good in sense of this transport regulation.

Packing group: No dangerous good in sense of this transport regulation.

Environmental hazards

Environmentally Hazardous: No.

Special precautions for user No information available.

**Transport in bulk according to
Annex II of MARPOL 73 / 78 and the IBC
Code:**

Not applicable.

**VF200PRO ADHESIVE INJECTION**

PART A

SECTION 15: REGULATORY INFORMATION**15.1 US REGULATIONS****National Inventory TSCA**

All ingredients in this material are included on or exempted from listing on the TSCA Inventory

National regulatory information

SARA Section 311/312 Hazards:

ethylene dimethacrylate (97-90-5): Immediate (acute) health hazard

Methacrylic acid, monoester with propane-1,2-diol (27813-02-1): Immediate (acute) health hazard

1,1'-(p-Tolylimino)dipropan-2-ol (38668-48-3): Immediate (acute) health hazard

15.2 STATE REGULATIONS**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Additional information

VOC content: 6,9 % (DIN EN ISO 11890-2)

SECTION 16: OTHER INFORMATION

Revision date: 26.06.2018

Version number: 1,04,2

Abbreviations and acronyms:

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

PEL: Permissible Exposure Limits

**VF200PRO ADHESIVE INJECTION**

PART A

SECTION 16: OTHER INFORMATION

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REL: Recommended Exposure Limits

VOC: Volatile organic compound

Other data:

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Disclaimer:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



VF200PRO ADHESIVE INJECTION

PART B

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: VF200PRO Versatile High-Load Adhesive Injection - PART B

1.2 RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Use of the substance/mixture: compound mortar B-component (hardener)

Uses advised against: No restriction

1.2 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier:	Allfasteners USA, LLC.	Fax: 201-783-8840
	480 Meadow Lane, Carlstadt, NJ 07072	Email: sales@allfasteners.com
	Phone: 888.859.6060	www.Allfasteners.com

1.3 EMERGENCY PHONE NUMBER

Emergency Telephone: 888.859.6060

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

29 CFR Part 1910.1200: Serious eye damage/eye irritation: Eye Irrit. 2A
Respiratory or skin sensitization: Skin Sens. 1

2.2 LABEL ELEMENTS

29 CFR Part 1910.1200:

Hazard Pictograms:



Signal Word: Warning

Hazard Statements: May cause an allergic skin reaction
Causes serious eye irritation

Precautionary statements: If medical advice is needed, have product container or label at hand.
Keep out of reach of children.

**VF200PRO ADHESIVE INJECTION**

PART B

2.2 LABEL ELEMENTS CONTINUED

Precautionary statements: Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
Dispose of contents/container to to in accordance with local/regional/national/international regulation.

Hazards not otherwise classified: This substance meets the PBT criteria of REACH, Annex XIII.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 MIXTURES****TABLE 4: MIXTURES**

HAZARDOUS COMPONENTS		
CAS NO.	COMPONENTS	QUANTITY
94-36-0	dibenzoyl peroxide; benzoyl peroxide	11.15 %

SECTION 4: FIRST-AID MEASURES**4.1 DESCRIPTION OF FIRST AID MEASURES**

General information: Change contaminated, saturated clothing.

After inhalation: Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin: After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes: After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion: Rinse mouth immediately and drink plenty of water.

Most important symptoms and effects, both acute and delayed: Allergic reactions

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

**VF200PRO ADHESIVE INJECTION**

PART B

SECTION 5: FIRE-FIGHTING MEASURES**5.1 EXTINGUISHING MEDIA**

Suitable extinguishing media: Co-ordinate fire-fighting measures to the fire surroundings.
Extinguishing powder.
Water spray jet.

Unsuitable extinguishing media: Full water jet.

5.2 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Pyrolysis products, toxic. Carbon monoxide.

5.3 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE - FIGHTERS

In case of fire and/or explosion do not breathe fumes. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 ADDITIONAL INFORMATION

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

Provide adequate ventilation. Use personal protection equipment. Special danger of slipping by leaking/spilling product.

6.2 ENVIRONMENTAL PRECAUTIONS

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Take up mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4 REFERENCE TO OTHER SECTIONS

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13



VF200PRO ADHESIVE INJECTION

PART B

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Advice on safe handling: Use only outdoors or in a well-ventilated area.
When using do not eat, drink or smoke.
Use protective skin cream before handling the product.

Advice on protection against fire and explosion: No special fire protection measures are necessary.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Requirements for storage rooms and vessels: Keep container tightly closed. Keep/Store only in original container.

Advice on storage compatibility: Do not use for products which come into contact with the food stuffs. Store in a well-ventilated place. Keep cool.

Further information on storage conditions: Keep container tightly closed in a cool place. Storage temperature 5-25°C.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS & EXPOSURE LIMITS

TABLE 5: CONTROL PARAMETERS & EXPOSURE LIMITS

EXPOSURE LIMITS						
CAS NO.	SUBSTANCE	PPM	MG/M ³	F/CC	CATEGORY	ORIGIN
94-36-0	Benzoyl peroxide	-	5		TWA (8 h)	PEL
		-	5		TWA (8 h)	REL
14808-60-7	Silica, crystalline (as respirable dust)	-	0.05		TWA (8 h)	REL
14808-60-7	Silica, crystalline quartz, respirable dust	(Z-3)	(Z-3)		TWA (8 h)	PEL

Additional advice on limit values: The contained quartz is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded.

8.2 EXPOSURE CONTROLS



Protective and hygiene measures: Remove contaminated, saturated clothing immediately. Draw up and observe skin protection program. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection: Suitable eye protection: Wear eye/face protection.

**VF200PRO ADHESIVE INJECTION**

PART B

8.2 EXPOSURE CONTROLS CONTINUED

Hand protection: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,4mm NBR (Nitrile rubber) >480min (EN374)

Wearing time with permanent contact 0,5mm NBR (Nitrile rubber) >480min (EN374)

Skin protection: Wear suitable protective clothing.

Respiratory protection: In case of inadequate ventilation wear respiratory protection.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Paste	Oxidizing properties	Not oxidising.
Color:	Black		Available oxygen content (%)
pH-Value:	Not applicable.		< 1%
Odor:	Characterisitc		no classification
Changes in the physical state		Vapor pressure:	Not determined.
Melting point/freezing point:	Not determined.	Density (at 20 °C):	1,59 g/cm ³
Initial boiling point & boiling range:	Not determined.	Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Flash point:	Not applicable.		
Flammability			
Solid:	Not determined.	Solubility in other solvents	Not determined.
Gas:	Not applicable.	Partition coefficient:	Not determined.
Lower explosion limits:	Not determined.	Vapor density:	Not determined.
Upper explosion limits:	Not determined.	Evaporation rate:	Not determined.
Auto-ignition temperature		Other information	
Solid:	Not determined.	Solid content:	Not determined.
Gas:	Not applicable.		
Decomposition temperature:	Not determined.		

**VF200PRO ADHESIVE INJECTION**

PART B

SECTION 10: STABILITY AND REACTIVITY

- Reactivity:** See section 10.3 (Possibility of hazardous reactions)
- Chemical Stability:** The product is stable under storage at normal ambient temperatures.
- Possibility of hazardous reactions:** Violent reaction with: Oxidising agent
- Conditions to avoid:** See section 7.2 (Handling and Storage)
- Incompatible materials:** Oxidising agent, strong.
- Hazardous decomposition products:** No known hazardous decomposition products.

SECTION 11: TOXICOLOGICAL INFORMATION & EFFECTS**11.1 INFORMATION ON TOXICOLOGICAL EFFECTS****TABLE 6: INFORMATION ON TOXICOLOGICAL EFFECTS****ACUTE TOXICITY**

CAS NO.	COMPONENTS				
	Exposure route	Dose	Species	Source	Method
94-36-0	dibenzoyl peroxide; benzoyl peroxide				
	oral	LD50 >5000 mg/kg	Rat		

- Carcinogenicity (OSHA):** No ingredient of this mixture is listed.
- Carcinogenicity (IARC):** Silica dust, crystalline, in the form of quartz or cristobalite (CAS 14808-60-7) is listed in group 1.
Benzoyl peroxide (CAS 94-36-0) is listed in group 3.
- Carcinogenicity (NTP):** No ingredient of this mixture is listed.

SECTION 12: ECOLOGICAL INFORMATION

- Ecotoxicity** The product is not: Ecotoxic.
- OECD 201 (Desmodesmus subspicatus)
- IC10: (0 - 72 h) = 30 mg/l
- IC50: (0 - 72 h) = 150 mg/l
- OECD 202 (Daphnia magna)
- EC0/NOEC (48h) = 100 mg/l
- EC50 (48h) = >500 mg/l
- EC100 (48h) = >>500 mg/l
- OECD 203 (Danio rerio)
- LC0/NOEC : 250 mg/l
- LC50 : > 500 mg/l
- LC100 : >> 500 mg/l

**VF200PRO ADHESIVE INJECTION**

PART B

SECTION 12: ECOLOGICAL INFORMATION CONTINUED

Persistence and degradability:	The product has not been tested.
Bioaccumulative potential:	The product has not been tested.
Mobility in soil:	The product has not been tested.
Other adverse effects:	No information available.
Further information:	Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 WASTE TREATMENT METHODS**

Advice on disposal: Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging: Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: TRANSPORT INFORMATION**US DOT 49 CFR 172.101**

Proper shipping name: Not a hazardous material with respect to these transport regulations.

Marine transport (IMDG)

UN number: No dangerous good in sense of this transport regulation.
UN proper shipping name: No dangerous good in sense of this transport regulation.
Transport hazard class(es): No dangerous good in sense of this transport regulation.
Packing group : No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number: No dangerous good in sense of this transport regulation.
UN proper shipping name: No dangerous good in sense of this transport regulation.
Transport hazard class(es): No dangerous good in sense of this transport regulation.
Packing group: No dangerous good in sense of this transport regulation.

Environmental hazards

Environmentally Hazardous: No.

Special precautions for user No information available.

**Transport in bulk according to
Annex II of MARPOL 73 / 78 and the IBC
Code:** Not applicable.

**VF200PRO ADHESIVE INJECTION**

PART B

SECTION 15: REGULATORY INFORMATION**15.1 US REGULATIONS****National Inventory TSCA**

All ingredients of this material are included on the TSCA Inventory.

National regulatory information

SARA Section 311/312 Hazards:

Benzoyl peroxide (94-36-0): Reactive, Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:

Benzoyl peroxide (94-36-0): De minimis limit = 1.0 %, Reportable threshold = Standard

15.2 STATE REGULATIONS**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

SECTION 16: OTHER INFORMATION**Revision date:**

26.06.2018

Version number:

1,02,0

Abbreviations and acronyms:

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations)

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

**VF200PRO ADHESIVE INJECTION**

PART B

SECTION 16: OTHER INFORMATION**Other data:**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Disclaimer:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.